



# ERW-XL

## ERW-XL

Removes iron stain quickly and completely.

Leaves surfaces clean, and streak free.

ERW-XL will remove even thick old layers of iron stain from nooks and crannies.

To use simply spray OR brush on, agitate, leave a short while and brush rinse off.

### Benefits of using ERW-XL

- Free of oxalic acid - uses new technology
- Very quick and effective
- Thick and foams so it clings - easy to use.
- Stays wet for a long time
- Leaves surfaces clean, streak-free and shiny
- Effective in hard or soft water
- Does not form white deposit with hard water
- Easily applied by brush or spray
- Removes old thick build up of iron dust
- Lifts off ordinary soil and grime
- Removes oil and grease



### Dilutions from concentrate

May be diluted with as much as nine volumes (10% v/v) of water depending on degree of soiling.

May be used with hard or soft water.

General wash	(Light contamination)	4 parts water to 1-part ERW-XL
Cleanse	(Medium contamination)	3 parts water to 1-part ERW-XL
Deep cleanse	(Heavy contamination)	2 parts water to 1-part ERW-XL
Refurbishment	(Scared and blistered)	1-part water to 1 part ERW-XL

### Methods of use Hand

Apply neat or diluted product with a pump-up spray. Agitate with a brush and allow to dwell for up to 30 minutes. Usually a few minutes is enough. Do Not allow to dry. Agitate again and brush rinse with low pressure water. Brush to aid rinsing if necessary.

Always use clean equipment.

### Rust and Browning Removal

Apply **ERW-XL** to structure with a brush. Agitate to create foam ensuring entire area is covered paying attention to hard to reach areas and fixings. Allow to dwell for 10 minutes.

Dampen brush with more solution and re-agitate solution. Allow to dwell for a further 5 minutes if required.

For heavily corroded areas, a mild abrasive cloth/ Scouring pad may be used in the same direction of the brush on the metal.

**Do not allow ERW-XL to dry on surface.**

Rinse down thoroughly with clear water, using a brush to aid rinsing. If any staining or corrosion remains, then repeat process to affected areas.

#### **\*Important\***

Rinse all areas by hand using the green microfiber cloth provided to remove all trace of ERW-XL. The solution must be fully removed; failure to do so may result in browning beneath the coating.

Do not use with other products.